

Kuhme Trailer 1108

QC FLEET # 8089-3
 # 1PMS34329C1005891
 OLD LINSEY # 414
 # UC GALLONS #

DIFFERENTIAL 1.1000 ENT HEAD DIMETER 1.1250
 CENTER DIMETER 2.000 ENT HEAD GALLONS 57
 CENTER HEAD GALLONS 132 INCREMENT 0.250

0 FT	1 FT	2 FT	3 FT	4 FT	5 FT	6 FT
0.00	8.28	835	1795	2165	2728	3106
0.25	9.	842	1510	2177	2758	3107
0.50	11.	853	1524	2190	2769	
0.75	12.	875	1538	2203	2779	
1.00	15.	899	1552	2217	2790	
1.25	17.	902	1566	2230	2799	
1.50	19.	911	1580	2243	2809	
1.75	21.	928	1594	2256	2819	
2.00	24.	941	1609	2269	2829	
2.25	27.	955	1623	2282	2839	
2.50	30.	968	1637	2295	2849	
2.75	33.	982	1651	2308	2858	
3.00	35.	983	1665	2321	2868	
3.25	39.	914	1679	2334	2877	
3.50	43.	925	1693	2347	2885	
3.75	47.	935	1707	2360	2895	
4.00	51.	947	1721	2373	2904	
4.25	55.	958	1736	2385	2912	
4.50	60.	969	1750	2398	2922	
4.75	64.	981	1764	2410	2932	
5.00	69.	992	1778	2423	2939	
5.25	74.	994	1792	2435	2947	
5.50	79.	915	1806	2448	2955	
5.75	85.	927	1820	2460	2963	
6.00	91.	938	1834	2472	2971	
6.25	96.	950	1848	2485	2979	
6.50	103.	962	1862	2497	2987	
6.75	109.	974	1876	2509	2994	
7.00	115.	985	1890	2521	3002	
7.25	122.	997	1904	2532	3009	
7.50	129.	1009	1918	2545	3016	
7.75	136.	1021	1932	2557	3023	
8.00	144.	1034	1945	2569	3029	
8.25	151.	1046	1959	2581	3036	
8.50	159.	1058	1973	2592	3042	
8.75	167.	1071	1987	2604	3048	
9.00	175.	1083	2000	2616	3054	
9.25	183.	1096	2014	2627	3060	
9.50	191.	1108	2028	2638	3065	
9.75	200.	1121	2042	2650	3071	
10.00	208.	1133	2055	2661	3076	
10.25	217.	1146	2069	2672	3081	
10.50	226.	1159	2083	2684	3085	
10.75	235.	1172	2096	2695	3089	
11.00	244.	1184	2109	2706	3093	
11.25	253.	1197	2123	2717	3097	
11.50	262.	1210	2137	2727	3102	
11.75	272.	1223	2150	2737	3105	

1108

NET INCHES

COMP # 1 & 3
 (FRONT & REAR)

2000 - 45"

2060 - 46"

COMPANIES VOLUME 3100
 RENT ADJUSTMENT FOR HANDLE OFFSETS 5000
 RATE CALIBRATION MAY BE NECESSARY FOR GREATER ACCURACY

Palumbo Trailer 1108

OC FEET # 8089-3
 S# 1PMS34329C1005891
 OLD HINDSEY # 414

HINDLE OFFSETS

5890

REAR HEAD DIAMETER 37.400
 REAR HEAD CENTER TO CENTER 42.000
 REAR HEAD SPLIT 0.000
 FRONT HEAD SPLIT 0.000
 FRONT HEAD CENTER TO CENTER 42.000
 FRONT HEAD DIAMETER 37.400

MIDDLE OPT = 2000 GALLON CAP
 # 1108

0 FT	1 FT	2 FT	3 FT	4 FT	5 FT	6 FT
0.00	1.181	510	904	1311	1681	1991
0.25	186	517	912	1319	1688	1998
0.50	192	525	923	1327	1695	2005
0.75	199	533	929	1336	1702	2011
1.00	204	541	938	1344	1709	2017
1.25	207	548	943	1352	1715	2022
1.50	215	556	955	1360	1722	2028
1.75	222	564	963	1368	1729	2034
2.00	228	572	972	1377	1736	2039
2.25	234	580	981	1385	1742	2044
2.50	241	588	989	1393	1749	2049
2.75	247	596	998	1401	1755	2054
3.00	253	604	1006	1409	1762	2059
3.25	260	612	1015	1417	1768	2064
3.50	266	620	1023	1425	1775	2069
3.75	272	628	1032	1432	1781	2074
4.00	279	636	1041	1441	1787	2079
4.25	286	644	1049	1449	1793	2084
4.50	292	653	1058	1457	1800	2089
4.75	299	661	1066	1465	1806	2094
5.00	306	669	1075	1473	1812	2099
5.25	313	677	1083	1480	1818	2104
5.50	319	685	1092	1489	1824	2109
5.75	326	694	1100	1496	1830	2114
6.00	333	702	1109	1504	1836	2119
6.25	340	710	1117	1512	1842	2124
6.50	347	718	1126	1519	1847	2129
6.75	354	727	1134	1527	1853	2134
7.00	361	735	1143	1535	1859	2139
7.25	369	743	1151	1542	1864	2144
7.50	375	752	1160	1550	1870	2149
7.75	383	760	1168	1557	1875	2154
8.00	391	768	1177	1565	1881	2159
8.25	401	777	1185	1572	1886	2164
8.50	409	785	1194	1580	1892	2169
8.75	417	794	1202	1587	1897	2174
9.00	425	802	1211	1595	1902	2179
9.25	434	810	1219	1602	1907	2184
9.50	441	819	1228	1610	1912	2189
9.75	449	827	1236	1617	1917	2194
10.00	456	836	1244	1624	1922	2199
10.25	464	844	1253	1631	1927	2204
10.50	471	853	1261	1639	1932	2209
10.75	479	861	1269	1646	1937	2214
11.00	487	870	1278	1653	1942	2219
11.25	494	879	1286	1660	1947	2224
11.50	494	887	1294	1667	1952	2229
11.75	502	895	1303	1674	1957	2234
12.00	509	903	1311	1681	1962	2239

ANNULAR OFFSETS = 0.0000
 DIMENSIONS AN ACTUAL
 NECESSARY FOR GREATER ACCURACY

FRONT
 10 FT INCHES

Comp # 2
 (MIDDLE)

1300 - 49